

### Flex Strip Series

# HFLX-SB60



**LM79 LM80**

### Features

- Can be cut at pre-marked soldering points
- Standard brightness
- Offers a variety of brightness, LED spacing and color temperatures
- Easy installation: wires pre-soldered & double-sided 3M™ tape for application
- For indoor signage, lighting enhancement, or decorative illumination
- Easy connect wires available ([download info here](#))

### Specifications

|                  |                              |
|------------------|------------------------------|
| Type             | LED flex strip               |
| Beam Angle       | 115°                         |
| Input Voltage    | 12vDC                        |
| Power            | 1m: 6w / 5m: 25w             |
| Length           | 5 m                          |
| Protection Grade | IP33                         |
| Packaging        | Anti-static bag              |
| Warranty         | 5 Year (Product)             |
| Operating Temp.  | -25 ~ +60 °C / -13 ~ +140 °F |
| Storage Temp.    | -25 ~ +70 °C / -13 ~ +158 °F |

| Color      | Part#          | Color Temp | Lumens   |
|------------|----------------|------------|----------|
| Pure White | HFLX-SB60WPURE | 6500K      | 420 lm/m |
| Day White  | HFLX-SB60WDAY  | 5000K      | 420 lm/m |
| Warm White | HFLX-SB60WWARM | 2800K      | 420 lm/m |
| Blue       | HFLX-SB60WBLUE | 470K       | 78 lm/m  |
| Red        | HFLX-SB60WRED  | 620K       | 76 lm/m  |

| MODEL      | MAX POWER SUPPLY LOAD |           |           |           |
|------------|-----------------------|-----------|-----------|-----------|
|            | 35W                   | 60W       | 100W      | 150W      |
| All models | 5 meters              | 10 meters | 16 meters | 25 meters |

### Profile Drawings

Max-Cascading Quantity: 5 meters

Unit: mm [in]

