

Ideal for Indoor Signage

Flex Strip Series

HFLX-SB60



LM79 LM80

Specifications

Viewing Angle	115°
Input Voltage	12VDC
Watts	1m (3.2ft): 6w 5m (16.4ft): 25w
Length	5m (16.4ft)
Protection Grade	IP20
Packaging	Anti-static bag
Warranty	5 Year (Product)
Operating Temp.	-25° ~ +60°C -13° ~ +140°F
Storage Temp.	-25° ~ -70°C -13° ~ +158°F

MAX Power Supply Load

Model	35W	60W	100W	120W	150W	240W
All Models	5 m 16.4 ft	10 m 32.8 ft	16 m 52.4 ft	20 m 65.6 ft	25 m 82 ft	40 m 131.2 ft

Color	Part #	Color Temp	Lumens
Pure White	HFLX-SB60WPURE	6500K	420 lm/m
Day White	HFLX-SB60WDAY	5000K	420 lm/m
Warm White	HFLX-SB60WWARM	2800K	420 lm/m
Blue	HFLX-SB60WBLUE	470nm	78 nm/m
Red	HFLX-SB60WRED	640nm	76 nm/m

Features:

- Can be cut at pre-marked soldering points
- Standard brightness
- Offers a variety of brightness, LED spacing and color temperatures
- Easy installation: wires pre-soldered & double sided 3M™ tape for application
- For indoor signage, lighting enhancement, or decorative illumination
- Easy connect wires available ([download info here](#))

Profile Drawings

Unit: mm [in]

